OTC -) DIDDE:	LIGHTING									
		S: COMPLY WITH APPROPRIATE SECTIONS TCATIONS FOR IMPORTANT TECHNICAL REQU	•				MPS. THE CATALOG NUMBERS LISTED				
		N CAREFULLY PREPARED TO ASSIST BIDDE									
		JRER SHALL COMPARE THE CATALOG NUME HITECT/ENGINEER OF ANY DISCREPANCIES.					·				
		ORIES TO FACILITATE INSTALLATION AS SHO									
		IES THAT WERE NOT REPORTED TO THE AR	•								
		NY AMBIGUITY IS THE RESPONSIBILITY OF T RE TYPES SHOWN WITHIN 48 BUSINESS HOL					•				
		EMPOWER THE ENGINEER TO DETERMINE FAI				•					
		INSTALLER. SUBMITTAL PACKAGE SHALL IN ED FIXTURES, PROVIDE A SECOND SET OF I									
		AT NO ADDITIONAL CHARGE. ALL FIXTURES									
		ITH THE LAMP AND BALLAST PROPOSED. C D ELECTRICAL DISTRIBUTOR SHALL VERIFY ⁻					·				
		E MAY OR MAY NOT INCLUDE LAMP(S) OR					S. UNIVERSAL VOLTAGE (120/277)				
LLAS	S REQUIF	UIRED UNLESS NOTED OTHERWISE. DIMENSION SEQUENCE = (LENGTH X WIDTH X DEPTH) IN INCHES. FIXTURE CHARACTERISTICS									
		BODY / AIR / MOUNTING / DOOR									
MBOL	MARK AS-1	LENS/LOUVER/REFLECTOR/OTHER USE DX-1 WITHOUT DC FILTERS	LAMP	WATTS	VOLTS	MANUFACTURE	R CATALOG NUMBER NOTE				
	CM	STEEL LINEAR FIXTURES: LENGTHS AND C	ONFIGURATIONS SHO	OWN ON	THE DRAWIN	NGS; LAMPS FOU	JR FOOT WHERE POSSIBLE;				
		PROGRAM START ELECTRONIC BALLASTS; T5 LAMPS; INTERNAL CONCEALED FASTENERS; COLOR AS NOTED AND/OR APPROVED BY ARCHITECT; ORIENT FIXTURE ACCORDING TO ARCHITECTS/ ENGINEER'S INSTRUCTIONS. SWIVEL STEM MOUNT UNLESS NOTED OTHERWISE. INSTALL LEVEL AND STRAIGHT WITH INVISIBLE SPLICES. PROVIDE ALL REQUIRED HANGERS, SPLICERS, END CAPS, JOINTS, FEEDS, ETC., FOR A COMPLETE INSTALLATION.									
	CM-14d	DIRECT/INDIRECT 8'	4–F28T5		277V	LIGHTOLIER	AG-C-8-P-WH-DS-2-28-277-PG-DIM				
		PENDANT.	RE835			NEORAY	52DIP/2T5-STXX-XX-8D-U-DB-DU-S85#				
		(2) 3-WIRE DIMMING BALLASTS				LITECONTROL	P-ID-59M48T5-PBSS/O-TCWM-LP /ELB-TW-2CWQ-ECSS-UNIV-DIM				
	CM-99	CORRIDOR RECESSED WALL WASH 6" WIDE LEGTH AS SHOWN	4-F28T5 RE841	130W	277V	LITECONTROL LIGHTOLIER	R-D-66N-48-T5-BWCWMSPECEB-UNV-STAGGERED PTS52SOUNV-8-S				
	DF	STAGGERED LAMPS FLUORESCENT DOWNLIGHT; THERMALLY PR	OTECTED HOUSING:	TO ACC	OMMODATE	MULTIPLE TRIMS	S AND REFLECTOR ASSEMBLIES				
		FOR LAMPS AS LISTED BELOW; ELECTRON									
	DF-14	#); SELF FLANGING TRIM UNLESS NOTED. RECESSED DOWNLIGHT; HORIZONTAL,	1-CF-A32	2 36W	277/120	V LIGHTOLIER	8031CLP-S6132BU				
		6" APERTURE, 32W CF—AMALGAM	RE835	- - ••	,120	PORTFOLIO	CD61242E 6CLH1421LI HB26				
		LAMP, CLEAR CONE.				GOTHAM	AF 1/32TRT 6AR MVOLT				
		CLEAR SELF TRIM.									
	DF-14d	RECESSED DOWNLIGHT; HORIZONTAL,	1-CF-A32	2 40W	277V	LIGHTOLIER	8031CLP-S6132BU-J2LD3				
		6" APERTURE, 32W CF-AMALGAM	RE835			PORTFOLIO	CD6142D42 6CLH1421LI HB26				
		LAMP, CLEAR CONE. CLEAR SELF TRIM.				GOTHAM	AF 1/32TRT 6AR MVOLT ADZT				
		CLEAN SEE THIN.									
	DF-15	RECESSED WALL WASHER;	1-CF-A32	2 36W	277/120	V LIGHTOLIER	8046CLP—S6132BU				
		6" APERTURE, HORIZONTAL LAMP, 1-32W CF-AMALGAM	RE835			PORTFOLIO GOTHAM	CLW6132E 6491LI HB26 DLWF 1/32TRT 6AR MVOLT				
		LAMP, CLEAR CONE.				GOTHAM	DEWI 17321KT OAK MIVOLT				
		CLEAR SELF TRIM.									
	DF-99	RECESSED DOWNLIGHT; HORIZONTAL,	1-CF-A18	3 24W	277V	POULSEN	BAL 1/18CF UNV-WHT				
		6" APERTURE, 32W CF—AMALGAM LAMP, CLEAR CONE. WHITE RING	RE841			LIGHTOLIER	8011CL-118VU-D4A04				
		BELOW CEILING, CLEAR SELF TRIM.									
	DX	LED MRI FIXTURES. REMOTE POWER SUPPL	Y. DC POWER TO E	NTER RO	OM THROU	GH RFI FILTERS	BY OTHERS.				
	DX-1	MRI LED COVE	LED	10W/FT	24VDC	ELECTRIX	L140 LUMILINE— HIGH OUTPUT				
		REMOTE POWER SUPPLY 544 LUMENS/FT	4000K			LUMENPULSE INSIGHT	LCSH024/120RMTpsXX40KFRXXXXWHDIM PL10W40K60HM48REMMWMRI/C1100PWRPL2				
		344 LOMENS/1 1				INSIGITI	TETOW TOROGENIA TORESINIA WINNEY OTTOOL WIN EZ				
	DX-2	MRI RECESSED LED 2X2	LED	75W	277/120	V GO EEL	S SERIES-GFS03T40				
		REMOTE POWER SUPPLY	4000K			KENALL	CSMRI22-G-C1-18L65K-24VDC-BLANK				
						INSIGHT	VT22 40K REM W MRI / C1 100 PWR				
	Е	E PREFIX INDICATES THAT FIXTURE IS PRO									
		4 OR 8 FOOT FLOURESCENT LAMP COMPA TO PROVIDE 90 MINUTES OF EMERGENCY					•				
		BE 1100 LUMENS OR HIGHER; UNIVERSAL 1	RANSFORMER FOR	120 OR .	277 VOLTS;	LOW VOLTAGE	PROTECTION, COMBINATION				
		TEST SWITCH AND AC "ON" INDICATOR; 10 NO DISASSEMBLY FOR TESTING.	J TEAK PRO-RATA	WARRAN	IY; INSTALI	L IEST SWITCH	IN A MANNER IHAI REQUIRES				
	E6	EXIT SIGN: CAST ALUMINIUM HOUSING; U									
	E6-1	GREEN LETTERS ON WHITE BACKGROUND; SINGLE FACE:	VANDAL RESISTANT LED	CONSTR 1W		JST MEET NFPA V DUAL-LITE	ILLUMINATION STANDARDS. LCSGW-VR				
					, =	LIGHTGUARD	DXLA1GW-VRS				
						LITHONIA SURE-LITES	LVS W 1 G 120/277 CAX-610085-GW				
						MCPHILBEN CHLORIDE	55L-1-12/27-WG-VL-TP CXLN1GW-VRS				
						LIGHTOLIER	LWA1GXW				
_	E6-2	DUAL FACE	LED	2W	120/277	V DUAL-LITE LIGHTGUARD	LCDGW-VR DXLA2GW-VRS				
						LITHONIA	LVS W 2 G 120/277				
						SURE-LITES MCPHILBEN	CAX-620085-GW 55L-2-12/27-WG-VL-TP				
						CHLORIDE	CXLN2GW-VRS				
	G	LIGHTOLIER LWA2GXW INDIRECT TROFFERS: RECESSED FOR LAY—IN GRID; HINGED FLUSH STEEL DOOR WITH LATCH; EARTHQUAKE CLIPS, PROGRAM START ELECTRONIC BALLASTS; LONG COMPACT FLUORESCENT LAMPS; ONE BALLAST PER FIXTURE, 100—10% DIMMING BALLAST									
	0.0	WHERE SHOWN.									
	G-2	2X4, 2-LAMP.	2–F32T8 RE835	56W	277/120	V FOCAL POINT	FBX-24-B-232-SP-120/277-G-PS-WH (5-1/2" DEPTH)				
			NEOOO			PRUDENTIAL	CL6038-24-232-X1-UNIVOLT-PROGRAM START				
						PMC	(6" DEPTH) SS24-RDI-T-232-4-PERF-WHT-12/27 (7" DEPTH				
						VISTA	S971120-232 2X4 EB PS				
						LSI	2LLGS 232 SS010PS RPW UE (5-1/2" DEPTH)				
						LITHONIA	T2AVG 232 MDR SMD MVOLT TUBRHP				
						Limonix	(5-1/2" DEPTH)				

	•	5" DEEP; SPECIFICATION						
GS-4	LAMPS; ONE BALLAST PER FIXTURE WHE 2X4, 3 LAMP.	3-F32T8 95W		/ LITHONIA	2 SP8G 332 A12125 1/3 MVOLT TUBRHP			
05 +	ZAT, O LAWII .	RE835	2///1201	LITTONIA	(4-1/2" DEPTH)			
		112000		METALUX	2GP-332A125-UNV-EB81-PROGRAM STAR			
					(3-3/4" DEPTH)			
				DAYBRITE	2DPG332-FS21-UNV-1/3EB-SPEC (4-3/8			
				COLUMBIA	ST824-332G-FSA12.125-3EB8LHPRUNV			
					(3-3/4" DEPTH)			
				LIGHTOLIER	XT2GVI332-UNV-03P (3-5/8" DEPTH)			
				LSI	LA125 332 SD SS010PS UE (4" DEPTH)			
S	FLUORESCENT STRIP LIGHT: STEEL CONS	TRUCTION; WHITE PAINTED	FINISH; SUITA	BLE FOR MOUN	NTING ON LOW DENSITY			
	CEILINGS; PROGRAM START ELECTRONIC LEVEL SWITCHING IS SHOWN ON THE PLA	•	E BALLAST PE	R FIXTURE WHI	ERE POSSIBLE, UNLESS TWO			
S-1	4', 2-LAMP STRIP LIGHT	2-F28T5 58W	277/120\	/ LITHONIA	Z2-28T5-MVOLT			
	,	RE841	,	NULITE	SA2-28T5-UNV-PS-N			
		NES II		BELFER	2825 28T5 2 E WH			
				LAL	MXAST200-14M-1E5-UNV			
SA	GENERAL PURPOSE INDUSTRIAL: WHITE E	NAMEL APERTURED REFLE	CTOR: PROCRA	M START FLE	CTRONIC BALLASTS: TRIAMPS:			
JA.	ONE BALLAST PER FIXTURE WHERE POSS	•	•					
	WITH TONG HANGERS.							
SA-2	8', 4-LAMP.	4-F32T8 120V	277/120\	/ LITHONIA	TEJA232-MVOLT-1/4TUBRHP-THUN			
	,	RE835	,	LIGHTOLIER	KW8A232-U-SOP			
				METALUX	8TIA-232-UNV-PROGRAM START			
				HUBBELL	IG184R-PP10-UPS			
				COLUMBIA	CSR8-232U-4EB8120/277 PROG-CSTH			
				DAYBRITE	TIA232-UNV-1/4-EB-SPEC			
SC	STAGGERED STRIP LIGHT: STEEL STRIP; RAPID START ELECTRONIC BALLASTS; T5 LAMPS; ONE BALLAST PER FIXTURE							
50	WHERE POSSIBLE; UNLESS TWO LEVEL SWITCHING IS SHOWN ON THE PLANS. SUITABLE FOR MOUNTING ON LOW DENSITY							
30	WHERE POSSIBLE; UNLESS TWO LEVEL S							
	WHERE POSSIBLE; UNLESS TWO LEVEL SY CEILINGS; PRIOR TO ORDERING FIXTURES	VERIFY COVE OR VALENCE	DIMENSIONS	FOR SUITABLE	SHIELDING AND SIZE.			
SC-1	WHERE POSSIBLE; UNLESS TWO LEVEL S		DIMENSIONS	FOR SUITABLE				
	WHERE POSSIBLE; UNLESS TWO LEVEL SY CEILINGS; PRIOR TO ORDERING FIXTURES	VERIFY COVE OR VALENCE	DIMENSIONS	FOR SUITABLE	SHIELDING AND SIZE.			
	WHERE POSSIBLE; UNLESS TWO LEVEL SY CEILINGS; PRIOR TO ORDERING FIXTURES 4', 1—LAMP STAGGERED STRIP	VERIFY COVE OR VALENCE 1-F28T5 31W	DIMENSIONS	FOR SUITABLE BARTCO NULITE	SHIELDING AND SIZE. BDS550-28/6/UNV/RS SA2-28T5-UNV-PS-N			
	WHERE POSSIBLE; UNLESS TWO LEVEL SY CEILINGS; PRIOR TO ORDERING FIXTURES 4', 1—LAMP STAGGERED STRIP	VERIFY COVE OR VALENCE 1-F28T5 31W	DIMENSIONS	FOR SUITABLE / BARTCO NULITE BELFER	SHIELDING AND SIZE. BDS550-28/6/UNV/RS SA2-28T5-UNV-PS-N 2825 28T5 2 E WH			
	WHERE POSSIBLE; UNLESS TWO LEVEL SY CEILINGS; PRIOR TO ORDERING FIXTURES 4', 1—LAMP STAGGERED STRIP	VERIFY COVE OR VALENCE 1-F28T5 31W	DIMENSIONS	FOR SUITABLE BARTCO NULITE	SHIELDING AND SIZE. BDS550-28/6/UNV/RS SA2-28T5-UNV-PS-N			
	WHERE POSSIBLE; UNLESS TWO LEVEL SY CEILINGS; PRIOR TO ORDERING FIXTURES 4', 1—LAMP STAGGERED STRIP	VERIFY COVE OR VALENCE 1-F28T5 31W	DIMENSIONS	FOR SUITABLE / BARTCO NULITE BELFER LAL	SHIELDING AND SIZE. BDS550-28/6/UNV/RS SA2-28T5-UNV-PS-N 2825 28T5 2 E WH			
SC-1	WHERE POSSIBLE; UNLESS TWO LEVEL SY CEILINGS; PRIOR TO ORDERING FIXTURES 4', 1-LAMP STAGGERED STRIP COVE; 6" OVERLAP 2', 1-LAMP STAGGERED STRIP	VERIFY COVE OR VALENCE 1-F28T5 31W RE835 1-F14T5 17W	DIMENSIONS 277/120V	FOR SUITABLE / BARTCO NULITE BELFER LAL / BARTCO	SHIELDING AND SIZE. BDS550-28/6/UNV/RS SA2-28T5-UNV-PS-N 2825 28T5 2 E WH MXAST200-14M-1E5-UNV			
SC-1	WHERE POSSIBLE; UNLESS TWO LEVEL SY CEILINGS; PRIOR TO ORDERING FIXTURES 4', 1-LAMP STAGGERED STRIP COVE; 6" OVERLAP	VERIFY COVE OR VALENCE 1-F28T5 31W RE835	DIMENSIONS 277/120V	FOR SUITABLE / BARTCO NULITE BELFER LAL / BARTCO NULITE	SHIELDING AND SIZE. BDS550-28/6/UNV/RS SA2-28T5-UNV-PS-N 2825 28T5 2 E WH MXAST200-14M-1E5-UNV BDS550-14/6/UNV/RS SAT-128T5-UNV-PS-N			
SC-1	WHERE POSSIBLE; UNLESS TWO LEVEL SY CEILINGS; PRIOR TO ORDERING FIXTURES 4', 1-LAMP STAGGERED STRIP COVE; 6" OVERLAP 2', 1-LAMP STAGGERED STRIP	VERIFY COVE OR VALENCE 1-F28T5 31W RE835 1-F14T5 17W	DIMENSIONS 277/120V	FOR SUITABLE / BARTCO NULITE BELFER LAL / BARTCO NULITE BELFER	SHIELDING AND SIZE. BDS550-28/6/UNV/RS SA2-28T5-UNV-PS-N 2825 28T5 2 E WH MXAST200-14M-1E5-UNV BDS550-14/6/UNV/RS SAT-128T5-UNV-PS-N 2825 14T5 2 E WH			
SC-1	WHERE POSSIBLE; UNLESS TWO LEVEL SY CEILINGS; PRIOR TO ORDERING FIXTURES 4', 1-LAMP STAGGERED STRIP COVE; 6" OVERLAP 2', 1-LAMP STAGGERED STRIP	VERIFY COVE OR VALENCE 1-F28T5 31W RE835 1-F14T5 17W	DIMENSIONS 277/120V	FOR SUITABLE / BARTCO NULITE BELFER LAL / BARTCO NULITE	SHIELDING AND SIZE. BDS550-28/6/UNV/RS SA2-28T5-UNV-PS-N 2825 28T5 2 E WH MXAST200-14M-1E5-UNV BDS550-14/6/UNV/RS SAT-128T5-UNV-PS-N			
SC-1	WHERE POSSIBLE; UNLESS TWO LEVEL SY CEILINGS; PRIOR TO ORDERING FIXTURES 4', 1-LAMP STAGGERED STRIP COVE; 6" OVERLAP 2', 1-LAMP STAGGERED STRIP	VERIFY COVE OR VALENCE 1-F28T5 31W RE835 1-F14T5 17W RE835	DIMENSIONS 277/120V	FOR SUITABLE / BARTCO NULITE BELFER LAL / BARTCO NULITE BELFER	SHIELDING AND SIZE. BDS550-28/6/UNV/RS SA2-28T5-UNV-PS-N 2825 28T5 2 E WH MXAST200-14M-1E5-UNV BDS550-14/6/UNV/RS SAT-128T5-UNV-PS-N 2825 14T5 2 E WH			
SC-2	WHERE POSSIBLE; UNLESS TWO LEVEL SY CEILINGS; PRIOR TO ORDERING FIXTURES 4', 1-LAMP STAGGERED STRIP COVE; 6" OVERLAP 2', 1-LAMP STAGGERED STRIP COVE; 6" OVERLAP DECORATIVE LUMINAIRE. DECORATIVE APPRIOR	VERIFY COVE OR VALENCE 1-F28T5 31W RE835 1-F14T5 17W RE835 PROVAL REQUIRED.	277/120V	FOR SUITABLE / BARTCO NULITE BELFER LAL / BARTCO NULITE BELFER LAL	SHIELDING AND SIZE. BDS550-28/6/UNV/RS SA2-28T5-UNV-PS-N 2825 28T5 2 E WH MXAST200-14M-1E5-UNV BDS550-14/6/UNV/RS SAT-128T5-UNV-PS-N 2825 14T5 2 E WH MXST200-1-2M-1ES-UNV			
SC-2	WHERE POSSIBLE; UNLESS TWO LEVEL SY CEILINGS; PRIOR TO ORDERING FIXTURES 4', 1-LAMP STAGGERED STRIP COVE; 6" OVERLAP 2', 1-LAMP STAGGERED STRIP COVE; 6" OVERLAP DECORATIVE LUMINAIRE. DECORATIVE APPEARED STRIP RECESSED TRIMLESS SLOT	VERIFY COVE OR VALENCE 1-F28T5 31W RE835 1-F14T5 17W RE835 PROVAL REQUIRED. 4-F32T8 110W	277/120V	FOR SUITABLE / BARTCO NULITE BELFER LAL / BARTCO NULITE BELFER LAL / ARCHITECTUR	SHIELDING AND SIZE. BDS550-28/6/UNV/RS SA2-28T5-UNV-PS-N 2825 28T5 2 E WH MXAST200-14M-1E5-UNV BDS550-14/6/UNV/RS SAT-128T5-UNV-PS-N 2825 14T5 2 E WH MXST200-1-2M-1ES-UNV			
SC-2	WHERE POSSIBLE; UNLESS TWO LEVEL SY CEILINGS; PRIOR TO ORDERING FIXTURES 4', 1—LAMP STAGGERED STRIP COVE; 6" OVERLAP 2', 1—LAMP STAGGERED STRIP COVE; 6" OVERLAP DECORATIVE LUMINAIRE. DECORATIVE APPRICATION OF THE PROPERTY OF THE PROPER	VERIFY COVE OR VALENCE 1-F28T5 31W RE835 1-F14T5 17W RE835 PROVAL REQUIRED.	277/120V	FOR SUITABLE / BARTCO NULITE BELFER LAL / BARTCO NULITE BELFER LAL	SHIELDING AND SIZE. BDS550-28/6/UNV/RS SA2-28T5-UNV-PS-N 2825 28T5 2 E WH MXAST200-14M-1E5-UNV BDS550-14/6/UNV/RS SAT-128T5-UNV-PS-N 2825 14T5 2 E WH MXST200-1-2M-1ES-UNV AL LPLR-DRY-CON/SP-8-S-STD-UNV-EXT-RKS			
SC-2	WHERE POSSIBLE; UNLESS TWO LEVEL SY CEILINGS; PRIOR TO ORDERING FIXTURES 4', 1-LAMP STAGGERED STRIP COVE; 6" OVERLAP 2', 1-LAMP STAGGERED STRIP COVE; 6" OVERLAP DECORATIVE LUMINAIRE. DECORATIVE APPEARED STRIP RECESSED TRIMLESS SLOT	VERIFY COVE OR VALENCE 1-F28T5 31W RE835 1-F14T5 17W RE835 PROVAL REQUIRED. 4-F32T8 110W	277/120V	FOR SUITABLE / BARTCO NULITE BELFER LAL / BARTCO NULITE BELFER LAL / ARCHITECTUR	SHIELDING AND SIZE. BDS550-28/6/UNV/RS SA2-28T5-UNV-PS-N 2825 28T5 2 E WH MXAST200-14M-1E5-UNV BDS550-14/6/UNV/RS SAT-128T5-UNV-PS-N 2825 14T5 2 E WH MXST200-1-2M-1ES-UNV			
SC-2	WHERE POSSIBLE; UNLESS TWO LEVEL SY CEILINGS; PRIOR TO ORDERING FIXTURES 4', 1-LAMP STAGGERED STRIP COVE; 6" OVERLAP 2', 1-LAMP STAGGERED STRIP COVE; 6" OVERLAP DECORATIVE LUMINAIRE. DECORATIVE APPRICATION OF THE PROPERTY OF THE PROPER	VERIFY COVE OR VALENCE 1-F28T5 31W RE835 1-F14T5 17W RE835 PROVAL REQUIRED. 4-F32T8 110W	277/120V	FOR SUITABLE / BARTCO NULITE BELFER LAL / BARTCO NULITE BELFER LAL / ARCHITECTUR LIGHTING WOF	SHIELDING AND SIZE. BDS550-28/6/UNV/RS SA2-28T5-UNV-PS-N 2825 28T5 2 E WH MXAST200-14M-1E5-UNV BDS550-14/6/UNV/RS SAT-128T5-UNV-PS-N 2825 14T5 2 E WH MXST200-1-2M-1ES-UNV AL LPLR-DRY-CON/SP-8-S-STD-UNV-EXT-RKS			
SC-2	WHERE POSSIBLE; UNLESS TWO LEVEL SY CEILINGS; PRIOR TO ORDERING FIXTURES 4', 1—LAMP STAGGERED STRIP COVE; 6" OVERLAP DECORATIVE LUMINAIRE. DECORATIVE APPRICATION OF THE PROPERTY OF THE P	VERIFY COVE OR VALENCE 1-F28T5 31W RE835 1-F14T5 17W RE835 PROVAL REQUIRED. 4-F32T8 110W RE35	277/120V 277/120V 277/120V	FOR SUITABLE / BARTCO NULITE BELFER LAL / BARTCO NULITE BELFER LAL / ARCHITECTUR LIGHTING WOF WALDMANN	SHIELDING AND SIZE. BDS550-28/6/UNV/RS SA2-28T5-UNV-PS-N 2825 28T5 2 E WH MXAST200-14M-1E5-UNV BDS550-14/6/UNV/RS SAT-128T5-UNV-PS-N 2825 14T5 2 E WH MXST200-1-2M-1ES-UNV AL LPLR-DRY-CON/SP-8-S-STD-UNV-EXT-RKS D14947000 LED 20 C L 1			
SC-2	WHERE POSSIBLE; UNLESS TWO LEVEL SY CEILINGS; PRIOR TO ORDERING FIXTURES 4', 1—LAMP STAGGERED STRIP COVE; 6" OVERLAP 2', 1—LAMP STAGGERED STRIP COVE; 6" OVERLAP DECORATIVE LUMINAIRE. DECORATIVE APP RECESSED TRIMLESS SLOT LIGHT. WHITE FROSTED LENS. CONTINUTOUS RUN. 4' EACH WALL. 8' CEILING. PROVIDED WITH INSIDE CORNERS. EXAM LIGHT CEILING MOUNTED	VERIFY COVE OR VALENCE 1-F28T5 31W RE835 1-F14T5 17W RE835 PROVAL REQUIRED. 4-F32T8 110W RE35	277/120V	FOR SUITABLE / BARTCO NULITE BELFER LAL / BARTCO NULITE BELFER LAL / ARCHITECTUR LIGHTING WOF	SHIELDING AND SIZE. BDS550-28/6/UNV/RS SA2-28T5-UNV-PS-N 2825 28T5 2 E WH MXAST200-14M-1E5-UNV BDS550-14/6/UNV/RS SAT-128T5-UNV-PS-N 2825 14T5 2 E WH MXST200-1-2M-1ES-UNV AL LPLR-DRY-CON/SP-8-S-STD-UNV-EXT-RKS D14947000 LED 20 C L 1 TE100-SC			
SC-2 TX-1	WHERE POSSIBLE; UNLESS TWO LEVEL SY CEILINGS; PRIOR TO ORDERING FIXTURES 4', 1—LAMP STAGGERED STRIP COVE; 6" OVERLAP DECORATIVE LUMINAIRE. DECORATIVE APPRICATION OF THE PROPERTY OF THE P	VERIFY COVE OR VALENCE 1-F28T5 31W RE835 1-F14T5 17W RE835 PROVAL REQUIRED. 4-F32T8 110W RE35	277/120V 277/120V 277/120V	FOR SUITABLE / BARTCO NULITE BELFER LAL / BARTCO NULITE BELFER LAL / ARCHITECTUR LIGHTING WOF WALDMANN	SHIELDING AND SIZE. BDS550-28/6/UNV/RS SA2-28T5-UNV-PS-N 2825 28T5 2 E WH MXAST200-14M-1E5-UNV BDS550-14/6/UNV/RS SAT-128T5-UNV-PS-N 2825 14T5 2 E WH MXST200-1-2M-1ES-UNV AL LPLR-DRY-CON/SP-8-S-STD-UNV-EXT-RKS D14947000 LED 20 C L 1			
SC-2 TX-1	WHERE POSSIBLE; UNLESS TWO LEVEL SY CEILINGS; PRIOR TO ORDERING FIXTURES 4', 1—LAMP STAGGERED STRIP COVE; 6" OVERLAP 2', 1—LAMP STAGGERED STRIP COVE; 6" OVERLAP DECORATIVE LUMINAIRE. DECORATIVE APP RECESSED TRIMLESS SLOT LIGHT. WHITE FROSTED LENS. CONTINUTOUS RUN. 4' EACH WALL. 8' CEILING. PROVIDED WITH INSIDE CORNERS. EXAM LIGHT CEILING MOUNTED	VERIFY COVE OR VALENCE 1-F28T5 31W RE835 1-F14T5 17W RE835 PROVAL REQUIRED. 4-F32T8 110W RE35	277/120V 277/120V 277/120V	FOR SUITABLE / BARTCO NULITE BELFER LAL / BARTCO NULITE BELFER LAL / ARCHITECTUR LIGHTING WOF WALDMANN	SHIELDING AND SIZE. BDS550-28/6/UNV/RS SA2-28T5-UNV-PS-N 2825 28T5 2 E WH MXAST200-14M-1E5-UNV BDS550-14/6/UNV/RS SAT-128T5-UNV-PS-N 2825 14T5 2 E WH MXST200-1-2M-1ES-UNV AL LPLR-DRY-CON/SP-8-S-STD-UNV-EXT-RKS D14947000 LED 20 C L 1 TE100-SC			

	N	
	NI ISSUED FOR CONSTRUCTION	2012-07-01
1 9 1 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	ASI /1	2013-03-25
foot	ADDENDUM #4 /->	2013-06-10
one		
	<u> </u>	
eighth in		
Ψ ——		
one O	Revisions:	Date
	VA FORM 08-6231	

"Engineering Results"

BHB Consulting Engineers

A Professional Corporation 2766 SOUTH MAIN STREET
SALT LAKE CITY, UTAH 84115
PHONE: 801.355.5656
FAX: 801.355.5950
EMAIL: blib@blibengineers.com Brett Goodman, PE LeedGA brett.goodman@bhbengineers.com

4

ARCHITECT/ENGINEERS: TRACY STOCKING & ASSOCIATES 17 Exchange Place, Salt Lake City, UT 84111 office: (801) 463-7103, mobile: (801) 541-7538 fax: (801) 463-7966, www.tsa-usa.com Tracy D. Stocking, AIA tracy@tsa-usa.com



324 S. State St., Suite 400 Salt Lake City, UT 84111 800-678-7077 801-328-5151 fax: 801-328-5155 www.spectrum-engineers.com

Project Title

CT SITE PREP Drawing Title Project Number LIGHTING FIXTURE SCHEDULE 660-CSI-104 Building Number Approved: Project Director Drawing Number VAMC - SALT LAKE CITY, UT EL601 OCTOBER 30, 2012 TXH Dwg. 56 of 59

Office of Construction and Facilities Management Department of Veterans Affairs

CONSULTANTS: